

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Agnew Bank	AB	7.0	UKC 25% until further notice Please refer to PPA Notice #230/21 for escort details										26-Mar-2021
Alliance East	AGE	10.8	214	15 cm/sec 0.29 knots	10°	DWT: 70,000t L _{OA} : 223.0m Beam: 31.90m Depth: ?? Draft: 13.35m	DWT: 20,000t L _{OA} : 157.0m Beam: 23.0m Depth: ?? Draft: 9.20m	DWT: 93,386t L _{OA} : 229.2m Beam: 38.04m Depth: No. info. S. Draft: 14.90m	DWT: 87,665t L _{OA} : 240.0m Beam: 38.0m Depth: No. info. S. Draft: 13.82m	SWL/Range of dolphin mooring: 50t, H-180°, V-30°; SWL/Range of caisson mooring: 100t, H-360°, V-30°; Refer to 'Notice to Industry 11/2016' for tidal current restrictions.	PPA NTI #11/2016 BCCP #21-008	30-Apr-2024	4-Jul-2025
Alliance West	AGW	10.6	218	15 cm/sec 0.29 knots	???	DWT: 70,000t L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 93,193t L _{OA} : 229.2m Beam: 38.04m Depth: No info. S. Draft: 14.90m	DWT: 93,193t L _{OA} : 229.2m Beam: 38.04m Depth: No info. S. Draft: 14.90m	SWL/Range of dolphin mooring: 50t, H-180°, V-30°; SWL/Range of caisson mooring: 100t, H-360°, V-30°; Refer to 'Notice to Industry 11/2016' for tidal current restrictions.		3-May-2021	20-Jan-2023
Allied Shipyard	ASY	2.7				N/A	N/A	N/A	N/A				1-Jan-1987
Campbell River Cruise (Wei Wai Kum)	CRC	10.0	311			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 4,200t L _{OA} : 217.75m Beam: 28.8m Depth: No info. S. Draft: 7.00m	DWT: 4,200t L _{OA} : 217.75m Beam: 28.8m Depth: No info. S. Draft: 7.00m	Ebb tide - Unrestricted. Flood tide - Less than 6 knot current at Seymour Narrows. No ship movement during first 40 minutes of flood tide.			15-Dec-2008
Nyrstar Discovery Terminal ex Campbell River Ore	CRO	10.0	173 Dolphin to Dolphin	10 cm/sec 0.19 knots	5°	Displ: 43,000t L _{OA} : 190.0m Beam: 30.0m Depth: No Info. Draft: No info.	DWT: No info. L _{OA} : No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 58,186t L _{OA} : 189.9m Beam: 32.26m Depth: No info. S. Draft: 12.93m	DWT: 53,828t L _{OA} : 190m Beam: 32.26m Depth: No info. S. Draft: 12.62m	Ebb tide - Unrestricted. Flood tide - Less than 6 knot current at Seymour Narrows. No ship movement at berth during first 40 minutes of flood tide. Vessel must have a minimum of 12 mooring lines (6 fwd. & 6 aft) SWL/Range of 4 x berthing dolphin bollards: 80t, H-180°, V-30°; SWL/Range of 2 x mooring buoys: 75t SWL/Range of 2 x onshore mooring bollards: 22t Minimum vessel size: 55m to 60m parallel midbody length; Max. air draft (freeboard) for loader at zero tide: 15m		6-Dec-2018	28-May-2019
Canada Place East	CPE	9.3	485	10 cm/sec 0.19 knots	5°	DWT: 80,000t L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 108,574t L _{OA} : 334.0m Beam: 42.8m Depth: No info. S. Draft: 15.00m	DWT: 12,000t L _{OA} : 348m Beam: 41.2m Depth: No. info. S. Draft: 8.82m			28-Apr-2021	20-Jan-2023
Canada Place North	CPN	11.8	270	10 cm/sec 0.19 knots	5°	DWT: 80,000t L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 13,294t L _{OA} : 289.6m Beam: 36.05m Depth: No info S. Draft: 8.50m	DWT: 10,420 L _{OA} : 294.49m Beam: 32.2m Depth: No info. S. Draft: 8.32m			28-Apr-2021	20-Jan-2023
Canada Place West	CPW	8.4	290	10 cm/sec 0.19 knots	5°	DWT: 80,000t L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 61,000t L _{OA} : 199.9m Beam: 32.24m Depth: No info. S. Draft: 13.00m	DWT: 8,604t L _{OA} : 300.1m Beam: 32.25m Depth: No info. S. Draft: 8.00m			25-Oct-2023	9-Feb-2024
Canexus / Nexen / Chemtrade aka Canadian Occidental	COC	10.0	150	7cm/sec at dolphin #3: 0.14 knots	Perpendicular to dock face	Displ: 93287t L _{OA} : 243.6m Beam: 32.3m Depth: 20.8m Draft: 14.5m	Displ: 74385t L _{OA} : 224.5m Beam: 32.2m Depth: 17.8m Draft: 12.5m	DWT: 62,915t L _{OA} : 209.28m Beam: 32.26m Depth: No info. S. Draft: 12.5m	DWT: 60,732t L _{OA} : 223.13m Beam: 32.2m Depth: No info. S. Draft: 13.02m	SWL/Range of shore mooring: 100t, H-???, V-45°; SWL/Range of dolphin mooring: 50t, H-???, V-??°; SWL/Range of floating mooring: 25t, H-???, V-??°; Shallow patch east of the range line east side of the dock; Berthing & unberthing: 1 knot window at 2nd Narrows; No consideration given for bow/stern thrusters.		25-Oct-2023	9-Feb-2024

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
Cargill 1	CG1	14.8	228 + 52	15 cm/sec 0.29 knots	≤15°	DWT: 70,000t L _{OA} : 250.0m Beam: 35.05m Depth: ?? Draft: 12.25m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 98,697t L _{OA} : 239.99m Beam: 38.04m Depth: No info. S. Draft: 14.48m	DWT: 75,471t L _{OA} : 243.47m Beam: 32.26m Depth: No info. S. Draft: 14.31m	16 shoreside mooring bollards, SWL: 72t		25-Nov-2020	26-Mar-2021
Cargill 2	CG2	10.2	205 + 52	15 cm/sec 0.29 knots	≤15°	DWT: 40,000t L _{OA} : 202.0m Beam: 28.04m Depth: ?? Draft: 11.6m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 64,000t L _{OA} : 199.9m Beam: 32.26m Depth: No info. S. Draft: 13.3m	DWT: 62,487t L _{OA} : 200.00m Beam: 32.3m Depth: No info. S. Draft: 13.36m	16 shoreside mooring bollards, SWL: 72t a) Max LOA 200m; Max BEAM 32.23m. b) If more than 10.5m draft, vessels not to be moored more than 180m East of the West end of the dock. c) If more than 11.5m draft, vessels not to be moored more than 160m East of the West end of the dock. Controlling depth is 10.0m if vessel is stern in and 11.0m if bow in.	BCCP #21-004	30-Apr-2024	25-Apr-2025
Cascadia	CAS	14.4	244	8 cm/sec 0.16 knots	??	DWT: 96,000t L _{OA} : 245m Beam: No Info. Depth: ?? Draft: ??	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 98,000t L _{OA} : 239.99m Beam: 38.04m Depth: No info. S. Draft: 14.58m	DWT: 45,025t L _{OA} : 243.47m Beam: 32.26m Depth: No info. S. Draft: 14.31m	Shoreside mooring SWL 100 tonnes; The tidal current restriction for berthing/unberthing at Cascadia is 2kts, with trials underway for up to 3 kts; No consideration given for bow/stern thrusters		25-Oct-2023	9-Feb-2024
Centerm 3	CT3	11.5	200			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:			29-Apr-2025	1-Aug-2025
Centerm 4	CT4	8.7	183			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:			25-Apr-2025	1-Aug-2025
Centerm 5	CT5	15.0	321	10 cm/sec 0.19 knots	5° at ¼ point	Displ: 192,500t L _{OA} : 368m Beam: 51.2m Depth: ?? Draft: 15.0m	DWT: 45,000t L _{OA} : 200m Beam: 31.0m Depth: ?? Draft: 11.5m	DWT: 131,304t L _{OA} : 363.6m Beam: 45.66m Depth: ?? S. Draft: 15.50m	DWT: 131,304t L _{OA} : 363.6m Beam: 45.66m Depth: ?? S. Draft: 15.50m	SWL/Range of shore mooring: 125t, H-???, V-??"; Distance between vessels: LOA up to 200m - 15 metres; Distance between vessels: LOA up to 250m - 20 metres Distance between vessels: LOA up to 300m - 25 metres Distance between vessels: LOA up to 350m - 30 metres	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	25-Apr-2025	1-Aug-2025
Centerm 6	CT6	15.4	324	10 cm/sec 0.19 knots	5° at ¼ point	Displ: 192,500t L _{OA} : 368m Beam: 51.2m Depth: ?? Draft: 15.0m	DWT: 45,000t L _{OA} : 200m Beam: 31.0m Depth: ?? Draft: 11.5m	DWT: 116,619t L _{OA} : 367.28m Beam: 42.8m Depth: ?? S. Draft: 15.0m	DWT: 115,993t L _{OA} : 371.0m Beam: 42.94m Depth: ?? Draft: 14.1m	SWL/Range of shore mooring: 125t, H-???, V-??"; SWL/Range of dolphin mooring: 125t, H-???, V-??"; Distance between vessels: LOA up to 200m - 15 metres; Distance between vessels: LOA up to 250m - 20 metres Distance between vessels: LOA up to 300m - 25 metres Distance between vessels: LOA up to 350m - 30 metres	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	21-Dec-2023	9-Feb-2024
Chemainus	CHN	11.7	213			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 61,860t L _{OA} : 200.0m Beam: 32.26m Depth: ?? S. Draft: 13.5m	DWT: 50,761t L _{OA} : 204.4m Beam: 32.31m Depth: ?? S. Draft: 12.64m	Terminal operator informs PPA that the berth is not in use.			3-Dec-2015
Cowichan Bay 1	CB1	8.8				DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 43,700t L _{OA} : 183.01m Beam: 31.15m Depth: ?? S. Draft: 12.0m	DWT: 37,450t L _{OA} : 185.5m Beam: 29.0m Depth: ?? S. Draft: 10.0m	Terminal operator informs PPA that the berth is not in use.			1-Nov-1995

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
Cowichan Bay 2	CB2					DWT: 47,069t LOA: 199.2m Beam: 30.6m Depth: ?? Draft: 11.8m	DWT: 27,104t LOA: 201.02m Beam: 30.87m Depth: ?? S. Draft: 11.52m			Terminal operator informs PPA that the berth is not in use.			
Crofton 1	CR1	9.2	163			DWT: 50,000t LOA: 213.4m Beam: 30.4m Depth: 17.3m Draft: 12.5m	DWT: 62,942t LOA: 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 50,197t LOA: 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m		PPA records show that no piloted vessel has docked at this berth in the last ten years.		2019	28-May-2019
Crofton 2	CR2	9.6	158	12 cm/sec 0.23 knots		DWT: 42,000t LOA: 182.9m Beam: 30.4m Depth: 17.3m Draft: 12.5m	DWT: 55,175t LOA: 190.0m Beam: 32.26m Depth: ?? S. Draft: 12.57m	DWT: 49,862t LOA: 208.78m Beam: 32.25m Depth: ?? Draft: 12.34m		Bow limit sign marker at barber pole. Bathymetry update from CHS on 22 March 2019.		2019	28-May-2019
Crofton 3	CR3	10.6	137	12 cm/sec 0.23 knots		DWT: 60,000t LOA: 273.0m Beam: 30.4m Depth: ?? Draft: ??	DWT: 20,157t LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 123,159 LOA: 349.0m Beam: 45.6m Depth: ?? S. Draft: 15.50m	DWT: 116,294 LOA: 349.07m Beam: 45.6m Depth: ?? S. Draft: 15.00m	Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m. Parallel berthing and do not exceed 10cm/sec berthing velocity for vessels larger than design vessel.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	18-Oct-2023	9-Feb-2024
DeltaPort 1	DP1	15.1	335	15cm/sec 0.29 knots	10°	DWT: 127,170t LOA: 366.0m Beam: 48.4m Depth: ?? Draft: 15.5m	DWT: 142,020t LOA: 366.52m Beam: 48.35m Depth: ?? S. Draft: 15.50m	DWT: 115,993t LOA: 366.89m Beam: 42.94 Depth: ?? S. Draft: 15.50m		Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m. Parallel berthing and do not exceed 10cm/sec berthing velocity for vessels larger than design vessel.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	18-Oct-2023	9-Feb-2024
DeltaPort 2	DP2	14.7	335	15cm/sec 0.29 knots	10°	DWT: 150,000t LOA: 380.0m Beam: 56.0m Depth: ?? Draft: ??	DWT: 20,000t LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 146,749t LOA: 365.9m Beam: 51.34m Depth: ?? S. Draft: 15.52m	DWT: 145,368t LOA: 368.04m Beam: 51.06m Depth: ?? S. Draft: 16.03m	Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016	26-Apr-2024	25-Apr-2025
DeltaPort 3	DP3	14.8	430	12.5cm/sec 0.24 knots	5°	DWT: 50,800t LOA: 213.4m Beam: 30.4m Depth: ?? Draft: 12.17m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 83,222t LOA: 229.0m Beam: 32.24m Depth: 17.00m S. Draft: 14.54m	DWT: 83,222t LOA: 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m	Berth is equipped with 200t mooring bollards for head/stern lines & 125t mooring bollards for spring lines. Turning basin off the berth has a limiting draft of 11.6m.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016		1-Mar-2009
Duke Point (Nanaimo)	DPT	13.7	170	15cm/sec 0.29 knots	Perpendicular to dock face	DWT: 50,800t LOA: 213.4m Beam: 30.4m Depth: ?? Draft: 12.17m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 83,222t LOA: 229.0m Beam: 32.24m Depth: 17.00m S. Draft: 14.54m	DWT: 83,222t LOA: 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m				

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated	
														Disclaimer: Berth information in these columns has been obtained from the terminal operators
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>														
Duncan Bay Paper	DBR	10.0 North 8.0 South				DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	<p>PPA records show that no piloted vessel has docked at this berth in the last ten years.</p> <p>NORTH Max 187.0m LOA or 32.2m beam.</p> <p>SOUTH a) Ships over 180.0m or 30.0m beam restricted to daylight only for arrival and the night departure restrictions. b) Ships over 25.0m beam without operating bowthruster restricted to daylight only for arrival and the night departures restrictions. c) Tug package is Cindy Mozel, Seymour Crown, and Carol Lee or equivalent for all vessels. d) Night departure restrictions (over 180m LOA or 25m beam w/out bow thruster): - Max draft of 9.0m. - One additional tug of at least 1200 HP will be provided. - Additional portable dock lighting. - Prevailing conditions taken into consideration.</p>			1-May-2006	
Duncan Bay Pulp	DBP	9.7				DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: 46,428t LOA: 198.0m Beam: 31.12m Depth: ?? S. Draft: 12.32m	DWT: 46,428t LOA: 198.0m Beam: 31.12m Depth: ?? S. Draft: 12.32m	<p>PPA records show that last piloted vessel docked at this berth in 2009.</p> <p>Tug package is Cindy Mozel, Seymour Crown, and Carol Lee or equivalent for all vessels.</p>			1-May-2006	
Esquimalt Graving Dock	EQG	8.8				DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: 52,357t LOA: 260.7m Beam: 32.25m Depth: ?? S. Draft: 12.50m	DWT: 8,604t LOA: 300.1m Beam: 32.25 Depth: ?? S. Draft: 8.00m	Length: 358.64m; Breadth: 38.4m; Depth: 11.5m (over sill)			1-Jan-1970	
Esquimalt North Wall	EQW	8.0				DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: 106,500t LOA: 240.5m Beam: 42.03m Depth: ?? S. Draft: 14.88m	DWT: 7,500t LOA: 294.13m Beam: 32.31m Depth: ?? S. Draft: 8.20m	Length: 244m			1-Oct-1998	
Esquimalt South Wall	EQS	6.6				DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: 12,782t LOA: 138.06m Beam: 21.37m Depth: ?? S. Draft: 8.00m	DWT: ?? LOA: 143.29 Beam: 21.7m Depth: ?? Draft: 7.46m	Length: 305m			1-Nov-2008	
Fibreco	FBR	13.0	220			DWT: LOA: Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: 92,710t LOA: 229.5m Beam: 36.97m Depth: ?? S. Draft: 14.70m	DWT: 92,710t LOA: 229.5m Beam: 36.97m Depth: ?? S. Draft: 14.70m	a) For arrival 2kt window for First Narrows. b) On departure over 8.5m draft OR 2kts at First Narrows will require two tractors. c) Lineboat always required at this berth for arrivals.		23-Apr-2025	1-Aug-2025	
First Narrows	FN	15.0	<p>First Narrows restricted only for vessels with over a 14.0m draft. Windows for such vessels are set for a two (2) knot current & 10% UKC for falling and rising tide. Airdraft restrictions start at: 56.57m for vessels with a beam of 45m or less 56.27m for vessels with greater than 45m beam.</p>									PPA Nti #02/2023		15-Jul-2015
Fraser River		9.5m Design Grade	<p>Due to the dynamic nature of the river agents must contact the dispatch office 24 hours prior to vessel arrival in the river to have their windows confirmed by the Pilot Committee. Outbound vessels must have their windows confirmed 12 hours prior to departure. Maximum vessel size in the river is 270m in length and 32.3m breadth. Special requests for vessels beyond this maximum size will be considered by the pilot committee on a case by case basis. The navigation channel is designed and maintained to provide a transit draft of 11.5m, always subject to tidal assist.</p>											
Fraser Surrey 1	FS1									Not in service				

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
Fraser Surrey 2	FS2	12.3	183			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 75,196t L _{OA} : 225.0m Beam: 32.3m Depth: ?? S. Draft: 14.25	DWT: 75,196t L _{OA} : 225.0m Beam: 32.3m Depth: ?? S. Draft: 14.25	Fraser Surrey 2-4 have a combined beam restriction of 53 meters for passing ships.			
Fraser Surrey 3	FS3	12.3	183			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 58,000t L _{OA} : 189.99m Beam: 32.26m Depth: ?? S. Draft: 12.40m	DWT: 23,930t L _{OA} : 193.8m Beam: 29.05m Depth: ?? S. Draft: 11.20m	Fraser Surrey 2-4 have a combined beam restriction of 53 meters for passing ships.			
Fraser Surrey 4	FS4	12.3	183			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 93,386t L _{OA} : 229.2m Beam: 38.04m Depth: ?? S. Draft: 14.9m	DWT: 87,665t L _{OA} : 240.0m Beam: 38.0m Depth: ?? S. Draft: 13.82m	Fraser Surrey 2-4 have a combined beam restriction of 53 meters for passing ships.			
Fraser Surrey 5	FS5									PPA records show that no piloted vessel has docked at this berth in the last ten years.			
Fraser Surrey 6	FS6	4.0	118							PPA records show that no piloted vessel has docked at this berth in the last ten years.			
Fraser Surrey 7	FS7	12.2	229			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 82,094t L _{OA} : 229.0m Beam: 32.3m Depth: ?? S. Draft: 14.47m	DWT: 67,145t L _{OA} : 294.17m Beam: 32.2m Depth: ?? S. Draft: 13.5m				
Fraser Surrey 8	FS8	12.2	229			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 67,145t L _{OA} : 294.17m Beam: 32.2m Depth: ?? S. Draft: 13.50m	DWT: 67,145t L _{OA} : 294.17m Beam: 32.2m Depth: ?? S. Draft: 13.50m				
Fraser Surrey 9	FS9	12.2	244			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 72,927t L _{OA} : 210.0m Beam: 36.0m Depth: ?? S. Draft: 13.84m	DWT: 65,919t L _{OA} : 294.12m Beam: 32.2m Depth: ?? S. Draft: 13.52m				
Fraser Surrey 10	FS10	11.0	65			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 75,378t L _{OA} : 224.98m Beam: 32.26m Depth: ?? S. Draft: 14.2m	DWT: 75,378t L _{OA} : 224.98m Beam: 32.26m Depth: ?? S. Draft: 14.2m	Finger Pier Structure (Berth Pocket 192m)			
Fraser Wharves	FW	10.7	153			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 59,217t L _{OA} : 199.9m Beam: 32.26m Depth: ?? S. Draft: 9.62m	DWT: 28,084t L _{OA} : 232.37m Beam: 32.26m Depth: ?? S. Draft: 10.02m	Vessels Often Overhangs Dock (Berth Pocket 310m)			
Gold River Pulp Dock (East)	GRE	10.9	152	10 cm/sec 0.19 knots	10° at ¼ point	Displ: 55,275t L _{OA} : 183.0m Beam: 31.1m Depth: 16.0m Draft: 12.0m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 55,183t L _{OA} : 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m	DWT: 55,183t L _{OA} : 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m	Pilot's discretion on transits during hours of darkness. Dolphin bollards: SWL 75t, H-180°, V-30°; Deck bollards: SWL 40t, H-180°, V-30°;			

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
Gold River Pulp Dock (West)	GRW	9.9				DWT: 10,000t LOA: 115.6m Beam: 17.5m Depth: No info. Draft: 14.9m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,744t LOA: 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	DWT: 37,744t LOA: 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	Pilot's discretion on transits during dark hours.			1-Oct-2010
Gold River Paper Dock	???	???	55.2 fendered section	15cm/sec 0.29 knots	6°	DWT: 10,000t LOA: 115.6m Beam: 17.5m Depth: No info. Draft: 14.9m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,744t LOA: 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	DWT: 37,744t LOA: 179.97m Beam: 29.8m Depth: ?? S. Draft: 10.54m	PPA records show no piloted assignments to this dock in over ten years.			
G3 Terminal	G3	14.8	283 dolphin to dolphin	10 cm/sec 0.19 knots	10°	Displ: 165,000 LOA: 293.0m Beam: 42.7m Depth: ?? Draft: 14.9m	Displ: 168,000 LOA: 168.0m Beam: 30.5m Depth: ?? Draft: 11.0m	DWT: 40,000t LOA: 168.0m Beam: 30.5m Depth: ?? S. Draft: 11.0m	DWT: 40,000t LOA: 168.0m Beam: 30.5m Depth: ?? S. Draft: 11.0m	Mooring Dolphins - SWL: 250t, H: 0° to 180°, V: 0° to 30°; Breasting Dolphins - SWL: 150t, H: 0° to 30° and 150° to 180°, V: 0° to 30°;		28-Apr-2025	1-Aug-2025
Harmac East - Island Terminals	HRE	9.9				DWT: 50,000t LOA: 223m Beam: 31.4m Depth: 17.0m Draft: 11.6m	DWT: 20,000t LOA: 165m Beam: 23.5m Depth: 12.8m Draft: 9.1m	DWT: 83,222t LOA: 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m	DWT: 83,222t LOA: 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.54m		PPA NTI #05/2016		1-Sep-1993
Harmac West - Pulp	HRW	10.2	122	15 cm/sec 0.29 knots	10° at ¼ point	DWT: 50,000t LOA: 223m Beam: 31.4m Depth: 17.0m Draft: 11.6m	DWT: 20,000t LOA: 165m Beam: 23.5m Depth: 12.8m Draft: 9.1m	DWT: 62,942t LOA: 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 50,197t LOA: 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m	SWL/Range of shore mooring: 68t, H-360°, V-30°;			1-Nov-1993
Imperial Oil - loco	IOC	8.0	150	7cm/sec 0.14 knots	up to 6,000t - 7° up to 15,000t - 2°	DWT: 15,000t LOA: 135.0m Beam: 33.5m Depth: No Info. Draft: 8.8m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,713t LOA: 180m Beam: 32.28m Depth: No info. S. Draft: 10.54m	DWT: 32,401t LOA: 180.9m Beam: 30.0m Depth: No info. S. Draft: 9.82m	Vessels with an arrival displacement > 6,000 MT may only berth from one hour before to one hour after high tide.		23-Apr-2025	1-Aug-2025
Lantic (BC Sugar)	BCS	6.5	130	10 cm/sec 0.19 knots	Perpendicular to dock face	DWT: 40,000t LOA: 200.0m Beam: 30.0m Depth: ?? Draft: 11.0m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 37,713t LOA: 180m Beam: 32.28m Depth: No info. S. Draft: 10.54m	DWT: 32,401t LOA: 180.9m Beam: 30.0m Depth: No info. S. Draft: 9.82m			23-Oct-2023	9-Feb-2024

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
LNG Canada Berth # 1 (ex Eurocan Berth 2) Kitimat	KLK1	TBA				DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	TBA			
LNG Canada Berth # 2 (ex MOF East) Kitimat	KLK2	13.4	430	0.1 m/sec	6 deg	DWT:107,000t L _{OA} :315m Beam:55m Depth: Draft:12m	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	Mooring system at Berth 2 consists of: • Six (6) mooring dolphins MD1, MD3, MD4, MD6 – Triple 150T QRH with dual Speed 2T capstans And MD2, MD5 – Quadruple 150T QRH with dual Speed 2T capstans, top of deck elevation at 8.17 m CD • Four (4) breasting dolphins (BD1 to BD4) double 150T QRH with dual speed 2T capstan, top of deck elevation at 8.1 m CD • Four (4) fenders (F1 to F4), equipped on four (4) breasting dolphins • Ten (10) mooring hook assemblies installed on top of each dolphin, 0.4 m above dolphin heights (assumed in this study) • Distance of 30 m from berthing line to hook assemblies on mooring dolphins • Distance of 5 m from berthing line to hook assemblies on breasting dolphins		1-Oct-2023	25-Apr-2025
LNGC MOF Jetty North	KMON	10.1	227			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	The berth face is fitted with 17 bollards & 18 fenders. All ships with a working fitted bow thruster should use, as a minimum, one ASD and one conventional 1800 HP twin-screw tug. Ships with no bow thruster should use two ASD tugs. All RO-RO modular ships should use two ASD tugs. Do not dredge a ship's anchor in the basin.			14-Feb-2021
LNGC MOF Jetty West	KMOW	10.3	239			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	The berth face is fitted with 18 bollards & 17 fenders. All ships with a working fitted bow thruster should use, as a minimum, one ASD and one conventional 1800 HP twin-screw tug. Ships with no bow thruster should use two ASD tugs. All RO-RO modular ships should use two ASD tugs. Do not dredge a ship's anchor in the basin.			14-Feb-2021
Lynn Terminal 1 (ex Lynn Terminal 4)	LT1 ex LT4	11.9	235			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 56,816t L _{OA} : 199.9m Beam: 32.2m Depth: ?? S. Draft: 13.52m	DWT: 50,197t LOA: 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m		PPA NTI #06/2016	25-Apr-2025	1-Aug-2025
Lynn Terminal 2 (ex Lynn Terminal 5)	LT2 ex LT5	15.0	240			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 96,027t L _{OA} : 243.0m Beam: 38.04m Depth: ?? S. Draft: 14.52m	DWT: 96,027t LOA: 243.0m Beam: 38.04m Depth: ?? S. Draft: 14.52m		PPA NTI #06/2016	28-Apr-2025	1-Aug-2025
Lynn Terminal 3 (ex Lynn Terminal 6)	LT3 ex LT6	14.6	240			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 81,955t L _{OA} : 228.99m Beam: 32.26m Depth: ?? S. Draft: 14.43m	DWT: 81,955t LOA: 228.99m Beam: 32.26m Depth: ?? S. Draft: 14.43m		PPA NTI #06/2016	29-Apr-2025	1-Aug-2025

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Lynn Terminal 4 (Univar) (ex Lynn Terminal 7)	LT4 ex LT7	11.7	200			DWT: 55,000t L _{OA} : 213m Beam: 32.0m Depth: 20.0m Draft: 12.0m	DWT: 40,300t L _{OA} : 171m Beam: 25.4m Depth: 15.7m Draft: 11.4m	DWT: 44,999t L _{OA} : 184.0m Beam: 32.23m Depth: ?? S. Draft: 13.0m	DWT: 36,677t L _{OA} : 184.33m Beam: 27.44m Depth: ?? S. Draft: 11.32m	The minimum number of lines required is 4 bow lines, 4 stern lines and 4 spring lines with 2 on the forward section and 2 on the aft section of the vessel. The maximum line pull on all bollards is 75 tonnes Arrivals: a) Lineboat always required b) Stbd. side to - slack water to 1kt ebb at 2 nd Narrows c) Port side to - slack water to 2kt ebb at 2 nd Narrows. Departures: Slack water 2kt ebb at Second Narrows.	PPA NTI #07/2016	25-Apr-2025	1-Aug-2025
Main Street Dock	MSD	4.3	108			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 679t L _{OA} : 46.8m Beam: 11.9m Depth: ?? S. Draft: 6.26m	DWT: 679t L _{OA} : 46.8m Beam: 11.9m Depth: ?? S. Draft: 6.26m	PPA records show that last piloted vessel docked at this berth was in 2013.		2-May-2024	25-Apr-2025
Nanaimo Assembly "A"	NSA	9.2	183							PPA records show that no piloted vessel has docked at this berth in the last ten years.			1-Jan-2002
Nanaimo Assembly Approach		9.0								5% on a rising tide; 10% on a falling tide.			1-Sep-2010
Nanaimo Assembly "B"	NSB	12.0	183			Displ: 37,945t L _{OA} : 200.0m Beam: 32.26m Depth: No. info. Draft: 9.0m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 55,183t LOA: 189.99m Beam: 32.3m Depth: ?? S. Draft: 12.57m	DWT: 17,100t L _{OA} : 199.99m Beam: 32.26m Depth: ?? S. Draft: 9.60m	Controlling Depth for arrival / departures is 8.0m. Two mooring dolphins north of berths B & C are fitted with 100t double bitt bollard. Wharf mooring bollards : SWL 30t			1-Jan-2002
Nanaimo Assembly "C"	NSC	11.7	183			Displ: 37,945t L _{OA} : 200.0m Beam: 32.26m Depth: No. info. Draft: 9.0m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 55,183t LOA: 189.99m Beam: 32.26m Depth: ?? S. Draft: 12.57m	DWT: 49,924t L _{OA} : 208.73m Beam: 32.2m Depth: ?? S. Draft: 12.34m	Controlling Depth for arrival / departures is 9.0m. Two mooring dolphins north of berths B & C are fitted with 100t double bitt bollard. Wharf mooring bollards : SWL 30t			1-Dec-2003
Nanaimo Passenger Terminal	NPT	10.0	230	15cm/sec 0.29 knots	Perpendicular to dock face	Displ: 69,100t L _{OA} : 312.0m Beam: 48.0m Depth: ?? Draft: 8.8m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 11,928t L _{OA} : 294.0m Beam: 32.3m Depth: ?? S. Draft: 8.30m	DWT: 9,500t L _{OA} : 317.25m Beam: 36.8m Depth: ?? S. Draft: 8.30m				1-Sep-2012
Neptune 1	NP1	18.1	230			DWT: 100,000t L _{OA} : 185.32m Beam: 43.66m Depth: Draft: 15.24m	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 208,000t L _{OA} : 299.97m Beam: 50.00m Depth: ?? S. Draft: 18.47	DWT: 208,000t L _{OA} : 299.97m Beam: 50.00m Depth: ?? S. Draft: 18.47	Lineboat required for arrivals and departures. Apply Neptune Bank (inner harbour) UKC guidelines as applicable.	BCCP #23-005	25-Apr-2025	12-Nov-2025
Neptune 2	NP2	15.4	229			DWT: 65,000t L _{OA} : 178.61m Beam: 39.93m Depth: Draft: 14.63m	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 83,688t L _{OA} : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.52m	DWT: 81,920t L _{OA} : 229.99m Beam: 32.29m Depth: ?? S. Draft: 14.43m	Lineboat required for arrivals.		24-Apr-2025	12-Nov-2025

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated	
														Disclaimer: Berth information in these columns has been obtained from the terminal operators
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.														
Neptune 3	NP3	13.9	155			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 82,057t L _{OA} : 229.0m Beam: 32.3m Depth: ?? S. Draft: 14.5m	DWT: 81,586t L _{OA} : 229.07m Beam: 32.26m Depth: ?? S. Draft: 14.52m	Controlling Depth on Approach - 13.5M. Lineboat required for arrivals.		13-Jan-2025	12-Nov-2025	
Neptune Bank	NB	14.5	UKC 5% of draft on a rising tide and 10% on a falling tide. a) Please refer to the VFPA Port Information Guide for First Narrows transit tug requirements. b) For vessels going to harbour anchorages, pilot must be ordered within windows that allow for UKC.											15-Jan-2019
Northland Cruise Terminal	NCT	21.2	325	15cm/sec 0.29 knots	6°	Displ: 58,000t L _{OA} : 313m Beam: 38.6m Depth: N/A Draft: 8.6m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: L _{OA} : Beam: Depth: S. Draft:	DWT: L _{OA} : Beam: Depth: S. Draft:	Mooring dolphins #1 & #8: SWL 100t, H-90°, V-30° Mooring dolphins #2 to #7: SWL 50t, H-180°, V-30°			1-May-2004	
Ogden Point North "A"	ONA	9.7	239	10 cm/sec 0.19 knots	2°	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 82,305t L _{OA} : 228.89m Beam: 32.31m Depth: ?? S. Draft: 14.58m	DWT: 8,293t L _{OA} : 261.31m Beam: 32.25m Depth: ?? S. Draft: 8.10m	Be aware of shoaling near bulkhead. Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2012	
Ogden Point North "B"	ONB	9.8	240		2°	DWT: 80,000t L _{OA} : 348m Beam: 41.4m Depth: Draft: 8.5m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 75,019t L _{OA} : 225.0m Beam: 32.31m Depth: ?? S. Draft: 14.2m	DWT: 10,749t L _{OA} : 317.25m Beam: 36.8m Depth: ?? S. Draft: 9.0m	On approach, 8.7m patch is 40m off the dock face. Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2013	
Ogden Point South "A"	OSA	10.1	298		2°	DWT: 80,000t L _{OA} : 348m Beam: 41.4m Depth: Draft: 8.5m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 75,356t L _{OA} : 224.95m Beam: 32.2m Depth: ?? S. Draft: 13.84m	DWT: 12,000t L _{OA} : 348.0m Beam: 41.2m Depth: ?? S. Draft: 8.82m	Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2012	
Ogden Point South "B"	OSB	9.7	239		2°	DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 31,727t L _{OA} : 176.82m Beam: 29.4m Depth: ?? S. Draft: 9.56m	DWT: 9,500t LOA: 317.25m Beam: 36.8m Depth: ?? S. Draft: 8.30m	Shoreside mooring bollards: Yellow - 200t at V=50°, Red - 100t at V=50°, Black - less than 50t at V=25° Shoreside mooring cleats: 15t at V=25° Dolphin with three hooks: 150t per hook at V=25° Dolphin with four bollards: 150t per bollard at V=25° Dolphin with one bollard: 250t per hook at V=25°	PPA NTI #06/2019		1-Oct-2012	
Pacific Elevator 4 Viterra	PE4	13.0	210	10cm/sec 0.19 knots	6°	DWT: 110,000t L _{OA} : 245m Beam: 38.05m Depth: 20.07m Draft: 14.9m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 87,337t L _{OA} : 225.0m Beam: 32.26m Depth: ?? S. Draft: 14.25m	DWT: 84,104t L _{OA} : 235.0m Beam: 32.29m Depth: ?? S. Draft: 14.6m	Mooring dolphins: SWL 150t, H-90°, V-30° Linear distance between North & South dolphins is 270m; UKC for rising tides is 5% and for falling tides is 10%. Official terminal name is Viterra Pacific Terminal.	BCCP #20-007	28-Apr-2025	1-Aug-2025	

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.													
Pembina Vancouver Wharves 1 ex Kinder Morgan 1	KM1	13.7	231			DWT: Panamax L _{OA} : 240m Beam: 32.0m Depth: Draft:	DWT: L _{OA} : 200m Beam: 34.0m Depth: Draft:	DWT: 83,478t L _{OA} : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.6m	DWT: 79,410t L _{OA} : 229.04m Beam: 32.26m Depth: ?? S. Draft: 14.62m	Shoreside mooring SWL range from 45t to 100t horizontal pull. Advise Master to keep ship's lines tight at all times. <u>Arrivals:</u> Loaded under 200m - 1kt window at 1 st Narrows. Loaded over 200m - slack water at 1 st Narrows. Light under 200m - 2kt window at 1 st Narrows. Light over 200m - 1kt window at 1 st Narrows. <u>Departures:</u> Loaded under 200m -2kt window at 1 st Narrows. Loaded over 200m - 1kt window at 1 st Narrows. Light: 2kt window at 1 st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	22-Nov-2023	9-Feb-2024
Pembina Vancouver Wharves 2/3 ex Kinder Morgan 2/3	KM2 KM3	11.4	317			DWT: 50,000t L _{OA} : 240m Beam: 32.0m Depth: Draft:	DWT: L _{OA} : 200m Beam: 34.0m Depth: Draft:	DWT: 83,478t L _{OA} : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.6m	DWT: 83,478t L _{OA} : 229.0m Beam: 32.24m Depth: ?? S. Draft: 14.6m	Shoreside mooring SWL range from 35t to 100t horizontal pull. Loaded: 2 knot window at First Narrows. Light: Under 200m Pilot's discretion; over 200m - 2kt window at 1st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	22-Nov-2023	9-Feb-2024
Pembina Vancouver Wharves 4 ex Kinder Morgan 4	KM4	12.8	161			DWT: Panamax L _{OA} : 230m Beam: 32.0m Depth: Draft:	DWT: L _{OA} : 183m Beam: 27.0m Depth: Draft:	DWT: 93,243t L _{OA} : 229.2m Beam: 38.02m Depth: ?? S. Draft: 14.9m	DWT: 77,673t L _{OA} : 243.82m Beam: 32.29m Depth: ?? S. Draft: 14.33m	Shoreside mooring SWL range from 45t to 150t horizontal pull. Starboard landings unless stated otherwise. Loaded: 2kt window at First Narrows. Light: Under 200m Pilot's discretion; over 200m - 2kt window at 1st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	22-Nov-2023	9-Feb-2024
Pembina Vancouver Wharves 5 ex Kinder Morgan 5	KM5	12.8	239			DWT: Panamax L _{OA} : 200m Beam: 34.0m Depth: Draft:	DWT: L _{OA} : 183m Beam: 27.0m Depth: Draft:	DWT: 82,500t L _{OA} : 229.0m Beam: 32.26m Depth: ?? S. Draft: 14.58m	DWT: 82,500t L _{OA} : 229.0m Beam: 32.26m Depth: ?? S. Draft: 14.58m	Shoreside mooring SWL range from 45t to 72t horizontal pull. 9.9m shoal 30m SE of VW5 dolphin / 11m on approach. Loaded: 2kt window at First Narrows. Light: Under 200m Pilot's discretion; over 200m - 2kt window at 1st Narrows. 2 knot restriction does not apply when shifting/warping (same side alongside)	PPA Notice 01-2020 has been archived. Information now in the port info. guide.	22-Nov-2023	9-Feb-2024
Parkland Marine Terminal ex Stanovan Refinery ex Chevron	STN	12.5	198			DWT: 50,000t L _{OA} : 310m Beam: 32.3m Depth: Draft:	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 61,328t L _{OA} : 213.36m Beam: 32.29m Depth: ?? S. Draft: 12.26m	DWT: 61,328t L _{OA} : 213.36m Beam: 32.29m Depth: ?? S. Draft: 12.26m	Shoreside mooring dolphin #1, #2, #5 & #6 are rated for 100t per hook. The hooks on dolphins #3 and #4 are normally used for spring lines and are rated for 50t each. Normal mooring pattern is 3-2-2 forward & aft. a) 210m between dolphins. b) 9.2m spot East of dock. c) 2kt window at 2nd Narrows. d) No consideration given for bow/stern thrusters. e) Order Times: Ebb tide 1hr before slack water. Flood tide 1hr order time before 1/2kt window providing that at order time current is 2kts or less		25-Oct-2023	9-Feb-2024
Port Alberni Assembly 1	AS1	10.4				DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 38,238t L _{OA} : 184.75m Beam: 30.6m Depth: ?? S. Draft: 10.0m	DWT: 38,238t L _{OA} : 184.75m Beam: 30.6m Depth: ?? S. Draft: 10.0m	Starboard side to only due to security fence.			1-Jul-2009

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated	
														Disclaimer: Berth information in these columns has been obtained from the terminal operators
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>														
Port Alberni Assembly 2	AS2	8.5				DWT: 55,183t LOA: 189.99m Beam: 32.3m Depth: ?? Draft: 12.57m	DWT: 55,183t LOA: 189.99m Beam: 32.3m Depth: ?? Draft: 12.57m						1-Aug-2001	
Port Alberni Assembly 3	AS3	12.2				DWT: 61,860t LOA: 200.0m Beam: 32.26m Depth: ?? Draft: 13.5m	DWT: 7,637t LOA: 219.4m Beam: 30.83m Depth: ?? Draft: 7.71m						1-Aug-2001	
Port McNeil (Orca Sand and Gravel)	PNL	15.4	150	16 cm/sec 0.30 knots;	5°	DWT: 88,500t LOA: 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 75,598t LOA: 244.72m Beam: 32.24m Depth: ?? S. Draft: 12.81m	DWT: 73,609t LOA: 246.91m Beam: 32.24m Depth: ?? S. Draft: 13.5m	Spring lines: 3 dolphins with SWL 100t; Breast lines: 4 buoys with SWL 75t, quick release hooks; Line boat required a) No current restrictions provided two tugs one of which is 30t BP (tractor) and one of which is a 20T bp (conventional) b) If no 30T tractor current limit of 1.5kts and 2x20t (1800HP) twin screw conventional tugs.			14-Mar-2019	
Port Mellon (HSPP Deep Sea Dock)	PML	9.1	189	15cm/sec 0.29 knots	15°	DWT: 73,000t LOA: 225.0m Beam: 32.3m Depth: No info. Draft: 13.3m	DWT: No info. LOA: No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 62,841t LOA: 199.98m Beam: 32.29m Depth: ?? S. Draft: 13.5m	DWT: 44,251t LOA: 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.29m	Length of deck apron (berth face) is 154m. SWL of mooring bollards on dock apron - 60t. SWL of east & west mooring bollards on shore - 100t.	PPA NTI #03/2017	12-Nov-2020	9-Feb-2021	
Port Moody Approach Channel		13.0	Approach channel width is 104 metres. UKC: 5% on a rising tide; 10% on a falling tide. Order times: Loaded & Turning - daylight and 2.5hrs before slack water at Second Narrows. All other vessels - 1.5hrs before slack water at Second Narrows. Second Narrows transit: Loaded vessels require 1hr from crossing Reed Point to make Second Narrows transit. If less than 1hr remaining, vessel will go to anchor.										19-Sep-2019	19-Nov-2019
Port Moody Turning Basin		12.9												
Pacific Coast Terminal Berth #1 (Bulk Liquids Berth) Port Moody	PM1	12.4	237	10cm/sec 0.19 knots	3°	DWT: 70,000t LOA: 241.0m Beam: 33.5m Depth: 18.28m Draft: 12.8m	DWT: 9,000t LOA: 132.6m Beam: 18.0m Depth: 10.67m Draft: 7.6m	DWT: 52,610t LOA: 195.03m Beam: 32.24m Depth: ?? S. Draft: 12.52m	DWT: 52,579t LOA: 195.13m Beam: 32.24m Depth: ?? S. Draft: 12.5m	Mooring bollards (both berths) SWL: 75 tonnes x 11; 100t x 1, 45t x 1 Berth No. 1 is the western portion of the continuous dock structure and is used for loading bulk liquids. Vessels are berthed port side to the dock. Information book: http://pct.ca/our-operations/vessel-information/		1-May-2024	25-Apr-2025	
Pacific Coast Terminal Berth #2 (Bulk Solids Berth) Port Moody	PM2	11.9	293	10cm/sec 0.19 knots	3°	DWT: 70,000t LOA: 241.0m Beam: 33.5m Depth: 18.28m Draft: 12.8m	DWT: 12,000t LOA: 141.7m Beam: 18.28m Depth: 10.97m Draft: 8.23m	DWT: 115,664t LOA: 254.0m Beam: 43.03m Depth: ?? S. Draft: 14.5m	DWT: 115,664t LOA: 254.0m Beam: 43.03m Depth: ?? S. Draft: 14.5m	Mooring bollards (both berths) SWL: 75 tonnes x 11; 100t x 1, 45t x 1 Berth No. 2 is the bulk solids loading facility. Vessels are berthed port side to the dock. Information book: http://pct.ca/our-operations/vessel-information/		1-May-2024	25-Apr-2025	
Prince Rupert Fairview South	PF2	16.6	400	20 cm/sec 0.39 knots; 15 cm/sec 0.29 knots; 12 cm/sec 0.23 knots	up to 34k tonnes - 10° at ¼ point berthing; 34k to 140k tonnes - 7.5° at ¼ point berthing; 146k to 200k tonnes - 5° at ¼ point berthing	Displ: 200,000t LOA: 380m Beam: 57.0m Depth: 29.0 Draft: 14.5m	Displ: 34,000t LOA: 180m Beam: 28.0m Depth: 16.1m Draft: 10.0m	DWT: 156,694t LOA: 366.0m Beam: 51.2m Depth: ?? S. Draft: 15.5m	DWT: 145,368t LOA: 368.04m Beam: 51.06m Depth: ?? S. Draft: 16.03m	SWL/Range of shore mooring: 150t, H-10° to 170°, V-0° to 30°; Fairview South 10% underkeel clearance.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #04-2017 PPA NTI #02/2016		2-May-2018	

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated	
														Disclaimer: Berth information in these columns has been obtained from the terminal operators
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>														
Prince Rupert Fairview North	PF4	16.6	400	20 cm/sec 0.39 knots; 15 cm/sec 0.29 knots; 12 cm/sec 0.23 knots	up to 34k tonnes - 10° at ¼ point berthing; 34k to 140k tonnes - 7.5° at ¼ point berthing; 146k to 200k tonnes - 5° at ¼ point berthing	DWT: 200,000t LOA: 380m Beam: 57.0m Depth: 29.0 Draft: 14.5m	DWT: 34,000t LOA: 180m Beam: 28.0m Depth: 16.1m Draft: 10.0m	DWT: 156,618t LOA: 366.0m Beam: 51.2m Depth: ?? S. Draft: 15.5m	DWT: 115,700t LOA: 367.28m Beam: 42.8m Depth: ?? S. Draft: 15.0m	SWL/Range of shore mooring: 150t, H-10° to 170°, V-0° to 30°; Fairview North 10% underkeel clearance.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #04-2023 PPA NTI #02/2016		2-May-2018	
Prince Rupert Westview Terminal (Pinnacle Pellets)	PWT	11.8	210	20cm/sec 0.39 knots	≤6°	Displ: 77,500t LOA: 245.0m Beam: 32.2m Depth: 20.0m Draft: 10.0m	DWT: No info. LOA: No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 82,688t LOA: 228.99m Beam: 32.26m Depth: ?? S. Draft: 14.4m	DWT: 81,601t LOA: 229.06m Beam: 32.26m Depth: ?? S. Draft: 14.45m	SWL of dolphin mooring 1 to 5: 150t, H-45° to normal, V-30° Line boat required, long spring, head & stern lines required (see tie-up plan under Berth Information).			2-Dec-2004	
Quatsino Narrows		HW 8.8 LW 6.1	Max LOA 185.9m; max beam 27.4m. 8.8m transit on HW slack daylight. 6.1m transit on any slack daylight.											1-Apr-1999
Richardson International ex James Richardson	JRI	12.9	183 + 37			DWT: 250,000t LOA: 325.0m Beam: 50.0m Depth: ?? Draft: 20.0m	DWT: No info. LOA: No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 98,681t LOA: 239.99m Beam: 38.0m Depth: ?? S. Draft: 14.45m	DWT: 87,665t LOA: 240.0m Beam: 38.0m Depth: ?? S. Draft: 13.82m	West mooring dolphin: SWL 50t, V-30° Breasting dolphin: SWL 50t, H-90°, V-30° Deck bollards: SWL 50t, H-180°, V-30° East mooring dolphin: SWL 50t, V-30°		16-May-2023	14-Oct-2023	
Ridley Island Coal	RIC	20.2				DWT: 250,000t LOA: 325.0m Beam: 50.0m Depth: ?? Draft: 20.0m	DWT: No info. LOA: No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 209,996t LOA: 299.99m Beam: 50.0m Depth: ?? S. Draft: 18.43m	DWT: 209,473t LOA: 300.0m Beam: 50.06m Depth: ?? S. Draft: 18.43m	For Panamax size vessels, two twin screw tugs equalling 5% of DWT spread equally over two bottoms. For Capesize two tractors of at least 50T BP are required.	PPA NTI #02/2019		1-Jan-2009	
Ridley Island Grain	RIG	14.2	240m; dolphin to dolphin	16 cm/sec 0.30 knots	≤10°	DWT: 100,000t LOA: 285.0m Beam: 42.0m Depth: ?? Draft: 16.0m	DWT: No info. LOA: No info. Beam: No info. Depth: No info. Draft: No info.	DWT: 93,328t LOA: 229.2m Beam: 38.04m Depth: ?? S. Draft: 14.9m	DWT: 76,279t LOA: 243.8m Beam: 32.2m Depth: ?? S. Draft: 14.02m	Mooring dolphins with quick release hooks; SWL: 100t	PPA NTI #05/2017		1-May-1985	
Rio Tinto Berth #1 (ex Rio Tinto Terminal A) Kitimat	KRT1	9.6	232	10 cm/sec 0.19 knots	5°	DWT: 219.0m LOA: 219.0m Beam: 35.0m Depth: ?? Draft: 16.0m	DWT: 219.0m LOA: 219.0m Beam: 35.0m Depth: ?? Draft: 16.0m	DWT: 63,878t LOA: 199.9m Beam: 32.26m Depth: ?? S. Draft: 13.33m	DWT: 49,862t LOA: 208.78m Beam: 32.25m Depth: ?? S. Draft: 12.34m	Dock elevation above MLLW is 8.9m; Max. height from waterline to top of hatch: 13.7m; Usual mooring pattern - Port side alongside, F: 3-1-2, A: 4-0-2, heaving line required; SWL of mooring bollards: 60t			24-Feb-2017	
Rio Tinto Berth #2 Kitimat	KRT2	13.5	230	15cm/sec 0.29 knots	6° (Panamax) 8° (Handysize)	DWT: 230.0m LOA: 230.0m Beam: 35.0m Depth: ?? Draft: 16.0m	DWT: 170.0m LOA: 170.0m Beam: 35.0m Depth: ?? Draft: 16.0m	DWT: 209,996t LOA: 299.99m Beam: 50.0m Depth: ?? S. Draft: 18.43m	DWT: 207,672t LOA: 311.92m Beam: 50.0m Depth: ?? S. Draft: 18.02m	Sixteen quick release hooks with capstans and remote release capability. One 4-hook unit (75 tonne capacity) on each dolphin. One 2-hook unit (75 tonne capacity) on each of the north and south corners of the berth face. Two double spring line hooks (60 tonne capacity) located near the center of the wharf. Additional mooring bollards (100 tonne capacity) spaced at 18.9 m centers.			20-Jan-2023	
Roberts Bank (Westshore) 1	RB1	22.2	295			DWT: 209,996t LOA: 299.99m Beam: 50.0m Depth: ?? S. Draft: 18.43m	DWT: 207,672t LOA: 311.92m Beam: 50.0m Depth: ?? S. Draft: 18.02m					26-Apr-2024	25-Apr-2025	

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated	
														Disclaimer: Berth information in these columns has been obtained from the terminal operators
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>														
Roberts Bank (Westshore) 2	RB2	19.0	170			DWT: 182,981t LOA: 291.95m Beam: 45.0m Depth: ?? Draft: 18.25m	DWT: 180,361t LOA: 295.05m Beam: 46.06m Depth: ?? S. Draft: 18.12m			Turning basin off the berth has a limiting draft of 11.6m.		18-Oct-2023	9-Feb-2024	
Sechelt	SCH	15.4		16cm/sec 0.31 knots	10°	DWT: 88,500t LOA: 225m Beam: 32.2m Depth: 19.5m Draft: 12.5m	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 74,973t LOA: 243.06m Beam: 32.29m Depth: ?? S. Draft: 13.92m	DWT: 73,609t LOA: 246.91m Beam: 32.24m Depth: ?? S. Draft: 13.5m	Four mooring buoys - proof load 100 tonnes; Three ship dolphins for berthing and mooring; Berth envelope is 300m x 32m to allow for warping a) Handymax inbound and outbound requires 1800hp tug, 2400hp tractor tug & lineboat; if working thruster, then 2400hp tractor & lineboat. b) Panamax inbound requires 1800hp tug, 2400hp tractor tug & lineboat, regardless of thruster c) Panamax outbound requires 900hp tug, 2400hp tractor tug & lineboat.			1-Jul-2003	
Second Narrows	SN	1. As per Second Narrows calculator. 2.85 x beam dictating the draft. 2. Air draft 44m (anything over 42m requires Air draft Survey) as per the Port of Vancouver's Port Information Guide. http://www.portvancouver.com/marine-operations/port-information-guide/												
Seymour Narrows	SNV	Slack water transits. Safe navigation clearance under Maud Island power cable is 58m. Maximum deep draft is 12m. Maximum LOA: Passenger vessel - 295m, Cargo vessel - 225m Loaded tankers the vessel's dimensions should not exceed 180 X 33 X 12.												
Shellburn	SHL	11.2	110	11 cm/sec 0.20 knots;	5°; ¼ point berthing;	Displ: 52,800t LOA: 218m Beam: Depth: Draft:	DWT: LOA: Beam: Depth: Draft:	DWT: 49,746t LOA: 183.06m Beam: 32.23m Depth: ?? S. Draft: 13.3m	DWT: 39,724t LOA: 183.2m Beam: 27.4m Depth: ?? S. Draft: 11.8m	SWL/Range of floating mooring: 75t, H-40°, V-20°; SWL/Range of dolphin mooring: 60t, H-45°, V-25°; SWL/Range of berthing dolphins: 20t, H-45°, V-15°; SWL/Range of berth cleats: 7.5t, H-90°, V-26°; All tankers require at least 10 mooring lines. a) 150m between buoys b) Order times 1.5hrs before slack at 2 nd Narrows.	BCCP #21-010	24-Apr-2025	1-Aug-2025	
Suncor/BPT/PetroCan - East	---	5.0	40		15°	Displ: 7,000t LOA: 85m Beam: No info. Depth: No info. Draft: No info.	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: LOA: Beam: Depth: S. Draft:	DWT: LOA: Beam: Depth: S. Draft:	The East dock (048° - 228°) is used to for small, domestic trading barges when the West berth is unavailable. Vessels to be berthed starboard side to. Pilot order times - 1.5hrs before slack water at 2nd Narrows.		27-Apr-2021	20-Jan-2023	
Suncor/BPT/PetroCan - West	PET	11.2	90	13.5 cm/sec 0.26 knots; 20.0 cm/sec 0.39 knots	20k to 66k tonnes - 5° Below 20k tonnes - 10°	Displ: 66,000t LOA: 222m Beam: No info. Depth: No info. Draft:	DWT: No Info. LOA: No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 74,905t LOA: 228.0m Beam: 32.29m Depth: ?? S. Draft: 14.57m	DWT: 74,898t LOA: 228.6m Beam: 32.26m Depth: ?? S. Draft: 14.17m	The West dock (049° - 229°) is the primary berth; all deep sea tankers berth at this dock starboard side alongside; Pilot order times - 1.5hrs before slack water at 2nd Narrows.		24-Apr-2025	1-Aug-2025	
Squamish 1	SQ1	10.9	137	10cm/sec 0.19 knots	10°; ¼ point berthing	Displ: 59,000t LOA: 204.4m Beam: 32.3m Depth: No info. Draft: 12.6m	Displ: 42,000 LOA: 193.3m Beam: 27.8m Depth: No info. Draft: 11.9m	DWT: 62,841t LOA: 199.98m Beam: 32.29m Depth: ?? S. Draft: 13.5m	DWT: 50,197m LOA: 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.32m	Mooring bollards on dock: SWL 75t, H-180°, V-30°, Mooring dolphins: SWL 140t, H-90°, V-30°, Controlling depth alongside 11.5m Controlling depth approaches 10.9m		15-Oct-2018	15-Jan-2019	

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Squamish 2	SQ2	10.3	152	11cm/sec 0.2 knots	¼ point berthing	Displ: 55,273t L _{OA} : 183m Beam: 31.1m Depth: 16.34m Draft: 12.0m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 62,942t LOA: 199.98m Beam: 32.26m Depth: ?? S. Draft: 13.51m	DWT: 44,251t LOA: 213.5m Beam: 31.0m Depth: ?? S. Draft: 12.29m	Mooring bollards on dock: 6 x 75t, H-180°, V-30°, Mooring dolphins F & A: 140t, H-90°, V-30°, Controlling depth alongside 11.4m Controlling depth approaches 10.3m		15-Oct-2018	15-Jan-2019
Stewart Bulk Terminal	STW	10.3	???	10 cm/sec 0.19 knots	Normal to dolphin face	DWT: 50,000t L _{OA} : 228.6m Beam: 30.5m Depth: No info. Draft: 11.6m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 63,656t LOA: 199.9m Beam: 32.3m Depth: ?? S. Draft: 13.32m	DWT: 50,827t LOA: 204.37m Beam: 32.3m Depth: ?? S. Draft: 12.64m	Berthing and unberthing at ore dock normally daylight only. Controlling depth for approach/departure is 9.7m.			14-Mar-2019
Stewart World Port	STP	13.8	210	15cm/sec 0.29 knots	10°; ¼ point berthing	Displ: 66,000t L _{OA} : 200.0m Beam: 32.0m Depth: ?? Draft: 12.0m	DWT: No Info. L _{OA} : No Info. Beam: No Info. Depth: No Info. Draft: No Info.	DWT: 54,123t LOA: 189.99m Beam: 32.26m Depth: ?? S. Draft: 12.44m	DWT: 50,748t LOA: 204.4m Beam: 32.3m Depth: ?? S. Draft: 12.64m	Shoreside mooring bollards have a SWL of 150t Starboard side to, daylight for arrivals and departures. Mooring buoy located approximately 40m off the south end for stern lines when going in starboard side alongside.			24-Jan-2019
Tahsis	TSS	11.4								PPA records show that no piloted vessel has docked at this berth in the last ten years.			
Texada Mines	TEX	14.0	183			DWT: 120,000t L _{OA} : 245.0m Beam: 43.0m Depth: ?? Draft: 15.4m	DWT: 70,000t L _{OA} : 224.0m Beam: 32.0m Depth: ?? Draft: 13.3m	DWT: 93,318t LOA: 229.2m Beam: 38.0m Depth: ?? S. Draft: 14.9m	DWT: 88,233t LOA: 229.93m Beam: 38.0m Depth: ?? S. Draft: 13.82m	Control depth for approach/departure is 12.5m.			1-Dec-2012
Vancouver Dry Dock	ZD1					DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 71,900t LOA: 228.6m Beam: 32.26m Depth: ?? S. Draft: 13.5m	DWT: 71,900t LOA: 228.6m Beam: 32.26m Depth: ?? S. Draft: 13.5m				
Vancouver Dry Dock Pier	VP1	10.0	170			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 175,292t LOA: 291.8m Beam: 45.0m Depth: ?? S. Draft: 18.25m	DWT: 175,292t LOA: 291.8m Beam: 45.0m Depth: ?? S. Draft: 18.25m				
Vanterm 4	VT4	8.8	183			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 52,610t LOA: 195.03m Beam: 32.24m Depth: ?? S. Draft: 12.52m	DWT: 52,579t LOA: 195.13m Beam: 32.24m Depth: ?? S. Draft: 12.5m		BCCP Notice #21-001	23-Apr-2025	1-Aug-2025
Vanterm 5	VT5	14.5	330			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 131,831t LOA: 347.48m Beam: 45.27m Depth: ?? S. Draft: 15.53m	DWT: 131,268t LOA: 361.61m Beam: 45.66m Depth: ?? S. Draft: 15.5m	Controlling depth will reduce to 10.5m when bow is closer than 30m from VT#4. Overall dock length of berths 5 & 6 is 610 metres.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016 BCCP Notice #21-011	24-Oct-2023	9-Feb-2024
Vanterm 6	VT6	14.8	280			DWT: L _{OA} : Beam: Depth: Draft:	DWT: L _{OA} : Beam: Depth: Draft:	DWT: 131,831t LOA: 347.48m Beam: 45.27m Depth: ?? S. Draft: 15.53m	DWT: 131,268t LOA: 361.61m Beam: 45.66 Depth: ?? S. Draft: 15.5m	Overall dock length of berths 5 & 6 is 610 metres.	PPA NTI #03/2018 PPA NTI #04/2018 PPA NTI #02/2016 BCCP Notice #21-011	24-Oct-2023	9-Feb-2024
						Displ: 21,500t	Displ:	Displ:	Displ:	Refer to Notice to Pilots #230/21 for berthing restrictions & tug requirements.	NtP #230/21		

Terminal/Berth Name	PPA Short Code	Controlling Depth (Meters)	Dock Length (Meters)	Maximum Berthing Velocity	Maximum Berthing Angle	Design Vessel Size (Largest)	Design Vessel Size (Smallest)	Largest DWT/Displ. from PPA Records	Longest Vessel from PPA Records	Guidelines & Remarks	Applicable Notices	Bathymetry Survey Date	Controlling Depth Last Updated
<p>Yellow highlight indicates that the information in the cell has been updated. Red text indicates that berthed vessel criteria exceeds berth's design vessel criteria. Green text indicates that berthed vessel criteria is within berth's design vessel criteria.</p>													
Watson Island (Porpoise Ch.) Pembina LPG Terminal	PWI	10.0	205	10 cm/sec 0.19 knots		L _{OA} : 170.0m Beam: 26.0m Depth: No info. Draft: 7.5m	L _{OA} : Beam: Depth: Draft:	L _{OA} : Beam: Depth: Draft:	L _{OA} : Beam: Depth: Draft:	Berth UKC restriction - no less than 0.9m. Porpoise Channel UKC 1.25 times draft. Minimum 12 mooring lines: 4 head/stern lines, 2 fwd./aft spring lines. All mooring bollards on the berth have a SWL rating of 50 tonnes.			
Westridge Terminal (New Berth #1)	WR1	15.4	330 <small>(end-to-end)</small>	12cm/sec 0.25 knot	7°	DWT: 120,000t L _{OA} : 250m Beam: 45m Depth: Draft: 13.5m	DWT: 17,300t L _{OA} : 115.8m Beam: 23.2m Depth: 23.2m Draft: 7.9m	Displ: L _{OA} : Beam: Depth: Draft:	Displ: L _{OA} : Beam: Depth: Draft:	Berth 1 consists of a loading platform, 4 berthing dolphins, and 6 mooring dolphins, three at each end. Average dock water density is 1.017 (subject to tides) Berth 1 has 27 mooring hooks. Each quick release mooring hook has a SWL of 100 tonnes. The berth is equipped with 4 berthing fenders and a docking aid system. UKC while alongside - 5% of static draft. UKC while docking/undocking - 10% of static draft.		26-Oct-2023	9-Feb-2024
Westridge Terminal (New Berth #2)	WR2	16.4	330 <small>(end-to-end)</small>	12cm/sec 0.25 knot	7°	DWT: 120,000t L _{OA} : 250m Beam: 45m Depth: Draft: 13.5m	DWT: 17,300t L _{OA} : 115.8m Beam: 23.2m Depth: 23.2m Draft: 7.9m	Displ: L _{OA} : Beam: Depth: Draft:	Displ: L _{OA} : Beam: Depth: Draft:	Berth 2 consists of a loading platform, 4 berthing dolphins, and 6 mooring dolphins, three at each end. Average dock water density is 1.017 (subject to tides) Berth 2 has 27 mooring hooks. Each quick release mooring hook has a SWL of 100 tonnes. The berth is equipped with 4 berthing fenders and a docking aid system. UKC while alongside - 5% of static draft. UKC while docking/undocking - 10% of static draft.		26-Oct-2023	9-Feb-2024
Westridge Terminal (New Berth #3)	WR3	19.2	330 <small>(end-to-end)</small>	12cm/sec 0.25 knot	7°	DWT: 120,000t L _{OA} : 250m Beam: 45m Depth: Draft: 13.5m	DWT: 17,300t L _{OA} : 115.8m Beam: 23.2m Depth: 23.2m Draft: 7.9m	Displ: L _{OA} : Beam: Depth: Draft:	Displ: L _{OA} : Beam: Depth: Draft:	Berth 3 consists of a loading platform, 4 berthing dolphins, and 6 mooring dolphins, three at each end. Average dock water density is 1.017 (subject to tides) Berth 3 has 27 mooring hooks. Each quick release mooring hook has a SWL of 100 tonnes. The berth is equipped with 4 berthing fenders and a docking aid system. UKC while alongside - 5% of static draft. UKC while docking/undocking - 10% of static draft.		26-Oct-2023	9-Feb-2024
Woodfibre	WDF	9.5								Not in service			1-May-2001
WWL Vehicle Service 1	AT1	10.7	212	17cm/sec 0.33 knot	0° flat berthing	Displ: 47,660t L _{OA} : 228.0m Beam: 32.3m Depth: 14.1m Draft: 11.0m	Displ: 22,630t L _{OA} : 164.0m Beam: 28.0m Depth: 12.0m Draft: 8.4m	DWT: 25,765t L _{OA} : 228.78m Beam: 32.26m Depth: ?? S. Draft: 10.0m	DWT: 26,985t L _{OA} : 232.39m Beam: 32.31m Depth: ?? S. Draft: 10.0m	See remarks under 'Fraser River' section Spring line mooring bollards: 80t, H-180°, V-45°; Bow/Stern/Breast line mooring bollards: 100t, H-Variou ^s , V-10°; Do not use shore mooring bollard No.6			
WWL Vehicle Service 2	AT2	10.7	200	17cm/sec 0.33 knot	0° flat berthing	Displ: 47,660t L _{OA} : 228.0m Beam: 32.3m Depth: 14.1m Draft: 11.0m	Displ: 22,630t L _{OA} : 164.0m Beam: 28.0m Depth: 12.0m Draft: 8.4m	DWT: 49,856t L _{OA} : 208.78m Beam: 32.256m Depth: ?? S. Draft: 12.34m	DWT: 25,818t L _{OA} : 228.78m Beam: 32.29m Depth: ?? S. Draft: 10.02	See remarks under 'Fraser River' section Spring line mooring bollards: 80t, H-180°, V-45°; Bow/Stern/Breast line mooring bollards: 100t, H-Variou ^s , V-10°; Do not use shore mooring bollard No.6			